



N-Ch 80V Fast Switching MOSFETs

Description

The HSU8048 is the high cell density trenched N-ch MOSFETs, which provide excellent RDSON and gate charge for most of the synchronous rectification applications.


The HSU8048 meet the RoHS and Halogen-Free compliant product requirement, 100% EAS guaranteed with full function reliability approved.

- 100% EAS Guaranteed
- Green Device Available
- Super Low Gate Charge
- Excellent CdV/dt effect decline
- Advanced high cell density Trench technology

Product Summary

V _{DS}	80	V
R _{DS(ON),TYP}	4.3	mΩ
I _D	48	A

TO-252 Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	80	V
V _{GS}	Gate-Source Voltage	±20	V
I _D @T _c =25°C	Continuous Drain Current, V _{GS} @ 10V _{1,6}	48	A
I _D @T _c =100°C	Continuous Drain Current, V _{GS} @ 10V _{1,6}	42.5	A
I _{DM}	Pulsed Drain Current ²	170	A
EAS	Single Pulse Avalanche Energy ³	57.8	mJ
I _{AS}	Avalanche Current	34	A
P _D @T _c =25°C	Total Power Dissipation ⁴	56	W
T _{STG}	Storage Temperature Range	-55 to 150	°C
T _J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance Junction-Ambient ¹	---	62	°C/W
R _{θJC}	Thermal Resistance Junction-Case ¹	---	2.2	°C/W



N-Ch 80V Fast Switching MOSFETs

Electrical Characteristics (T_J=25 °C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	80	---	---	V
R _{D(S)} (ON)	Static Drain-Source On-Resistance ₂	V _{GS} =10V , I _D =20A	---	4.3	6.5	mΩ
R _{D(S)} (ON)	Static Drain-Source On-Resistance ₂	V _{GS} =4.5V , I _D =20A	---	6.3	8.5	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	1.2	---	2.3	V
I _{bss}	Drain-Source Leakage Current	V _{DS} =64V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =64V , V _{GS} =0V , T _J =55°C	---	---	5	
I _{GS}	Gate-Source Leakage Current	V _{GS} =±20V , V _{DS} =0V	---	---	±100	nA
g _{fS}	Forward Transconductance	V _{DS} =5V , I _D =20A	---	75	---	S
R _G	Gate Resistance	V _{DS} =0V , V _{GS} =0V , f=1MHz	---	0.5	---	Ω
Q _G	Total Gate Charge (10V)	V _{DS} =40V , V _{GS} =10V , I _D =20A	---	40	---	nC
Q _{GS}	Gate-Source Charge		---	7.2	---	
Q _{GD}	Gate-Drain Charge		---	6.5	---	
T _{d(on)}	Turn-On Delay Time	V _{DD} =40V , V _{GS} =10V , R _G =3Ω, I _D =20A	---	8.3	---	ns
T _r	Rise Time		---	4.2	---	
T _{d(off)}	Turn-Off Delay Time		---	36	---	
T _f	Fall Time		---	6.9	---	
C _{iss}	Input Capacitance	V _{DS} =40V , V _{GS} =0V , f=1MHz	---	2860	---	pF
C _{oss}	Output Capacitance		---	410	---	
C _{rss}	Reverse Transfer Capacitance		---	38	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _s	Continuous Source Current _{1,5}	V _G =V _D =0V , Force Current	---	---	48	A
V _{SD}	Diode Forward Voltage ₂	V _{GS} =0V , I _s =A , T _J =25°C	---	0.77	1.0	V
t _{rr}	Reverse Recovery Time	I _F =20A , dI/dt=100A/μs , T _J =25°C	---	27	---	nS
Q _{rr}	Reverse Recovery Charge		---	89	---	nC

Note :

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
- 3.The EAS data shows Max. rating . The test condition is V_{DD}=25V,V_{GS}=10V,L=0.1mH,I_{AS}=34A
- 4.The power dissipation is limited by 150°C junction temperature
- 5.The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.
- 6.The maximum current rating is package limited.



Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs G-S Voltage




Fig.3 Source Drain Forward Characteristics




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J



N-Ch 80V Fast Switching MOSFETs




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Switching Waveform



Ordering Information

Part Number	Package code	Packaging
HSU8048	TO-252	2500/Tape&Reel



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP.		0.091 TYP.	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF.		0.150 REF.	